



FC SOFT



DESCRIPTION	Transfer paper for various light colored surfaces	
TECHNICAL DATA	FC SOFT is made of a 120 µm, 115 g/m ² natural paper liner , a 30 µm, 25 g/m ² polyolefin layer and a 4 µm composite polymer finish .	
EQUIPMENT	Color laser printer or copy machine + heat press	
SUITABLE FOR	Excellent for natural leather or wood . Can be used on coated fabrics or synthetic leather.	FEATURES

FC SOFT transfers a **very thin film that does not change the skin's natural feel** and the look of the leather. Once transferred, **the skin is ready for subsequent processing**. It needs protective resins or waxes for longer life.

INSTRUCTIONS	<p>1</p>	<p>Insert the transfer paper in the laser printer's by-pass and set to thick paper or cardboard printing mode (160-200 g/m²). Multicopy print. Print in mirror mode.</p>
	<p>2</p>	<p>Place the printed side of the transfer paper on the media. Possibly protect the transfer paper with a soft silicone mat (MA STUOI GB80-2).</p>
	<p>3</p>	<p><u>With protection</u></p> <p>Air press: 150°C for 40" - pressure 6atm</p> <p>Manual press: 150°C for 40" - very high pressure</p> <p><u>Without protection</u></p> <p>Air press: 120°C for 30" - pressure 6atm</p> <p>Manual press: 120°C for 30" - very high pressure</p>
	<p>4</p>	<p>Remove paper liner when cool.</p>

WARNINGS	<p>Do not machine wash. Acquires resistance to dry cleaning and excellent resistance to abrasion after appropriate tannery treatment. For further information contact your dealer.</p>	STORAGE
	<p>Store in a cool dry place.</p> <p>Do not expose to direct sunlight.</p> <p>If properly stored the product will maintain its features for at least 2 years.</p>	

The instructions on this sheet are merely indicative and contain details concerning tests carried out in our laboratories with our equipment. Do your own testing. The manufacturer will replace defective material but is not responsible for any damage resulting from incorrect use.

* Also available in 100/A4 packages

SHOCKLINE
about your transfer paper

T. +39 (0)875 751194 - F. +39 (0)875 751329
info@shockline.it - skype shock.line
www.shockline.it - www.digidecor.it

code